



“Commercial Gentleman” Automatic Commercial Door Opener

Low Energy Public Access

The Commercial Gentleman Public Access System provides the most cost effective door automation available for handicap access of swing doors in public places.

The system power opens the door and a built in closer brings the door closed. The door opener is pneumatically powered and is activated through pneumatic or low voltage controls. It works on any size of wood, metal, or glass door.



Key Features

- ✓ Easily retrofittable
- ✓ Does not interfere with the existing door hardware
- ✓ Easily installed and adjusted
- ✓ No increased resistance when using the door manually
- ✓ Low profile small compact header above the door, silent operation
- ✓ Extremely reliable – 1 year warranty
- ✓ Reacts immediately to any obstacle and opening door will stop at any point
- ✓ Activated by wall switches or remote control, pneumatic controls or low voltage controls
- ✓ Interfaces with the existing security systems such as maglocks and interphone systems
- ✓ No maintenance

Optional Features

- ✓ Touchless wall switches
- ✓ Integrated card readers and proximity card readers
- ✓ Pneumatic controls for non-electrical applications
- ✓ Vestibule entry systems – sequenced door activation

Specifications

Door Width	30” to 60” wide doors
Door Weight	up to 240lb door
Drive System	Pneumatics
Controller/Power	12/24 VDC or VAC or 110VAC Solenoid
Timer Modules	1 – 30 second delay (optional sequencing)
Cylinder Dia.	Diameter of cylinder 1 1/4”
Door Controls	Pneumatic or low voltage dry contact switches
Power required	2/24 VDC or VAC or 110VAC
Air Supply	90 -110 PSI
Opening	Entire width of sliding panel